



Trojan Products Care and Maintenance

Decorative Finish

To retain the highest corrosion resistance it is necessary to keep the surfaces clean. This can be done by wiping with a warm clean cloth using either a very mild detergent or soap only, then rinsing with warm clean water and drying with a soft cloth. Abrasive, chemical or brass cleaners, wire brushes, scrubbers and wire wool etc should not be used under any circumstances.

Keep clean and free from dirty deposits which may attack the finish. Avoid contact with sharp objects which may cut into the finish.

Moving Parts

Products with moving parts, such as handle rotation, sliders on runners and locking gear should be lubricated with a light machine oil or a Silicone spray lubricant at least twice a year. Where parts strike together, such as Shoot Bolt locking points into Retaining Keeps on Window locks for example, should be greased at least twice a year with an acid free lubricant such as Petroleum Jelly.

Keep clean and free from dirty deposits which may cause obstruction or attack the substrate. If moving parts have come into contact with contaminants, where possible blow the area clean with compressed air and re lubricate. If further cleaning is required, lightly spray with Silicone spray lubricant to flush out contaminated area and wipe clean with a soft cloth and re lubricate.

Fixed Parts

To ensure correct operation it is important that all products remain firmly fixed at all times. To this end they must be regularly inspected and where necessary screws and fixings should be repaired by a suitably qualified person.